

MF 系列-接管不锈钢接头说明书

MF Series - conduit cable gland

- **产品材料:** 默认 304, 可选 316 及 316L, 密封件为 EPDM 橡胶
- **防护等级:** 规定卡口范围内, 配合密封圈, 防护等级可达 IP68
- **工作温度:** 测试 -40° ~ 105° 零件无损坏且保障设备正常运转
- **阻燃等级:** UL94V-2, 可定制 V0 级阻燃
- **产品性能:** 内外丝接管设计, 内牙端可连接挠性管, 镀锌管等
- **订购说明:** 默认不附螺母, 如需 316 或 316L 材质, 请将型号后缀“SS”变更为“S316”或“S316L”

☆特别提示: 型号栏带*为非标产品, 可能无库存或只有少量库存

- **Materials:** 304. Can choose 316 and 316L are optional, And the seal is EPDM
 - **Waterproof:** Within the clamping range, The waterproof grade can reach IP68
 - **Temperature:** -40° ~ 105° , Short-term 120°
 - **fire prevention:** UL94V-2, Customizable V0
 - **performance:** Internal and external tooth design, the internal tooth end can be connected with flexible pipe and galvanized pipe
 - **Ordering Information:** Without nut, if 316 is required, please change the rear model Ss to s316
- ☆**Special tips:** The * in front of the model is a special product. There may be no or only a small amount of stock. You need to order in advance



应用场合/Application place



公制 M 螺纹/Metric thread

蓝江产品型号	外螺纹	内螺纹	电缆范围	螺纹长度	扳手尺寸	包装数量
Product model	M-thread	F-thread	Cable range	Thread length	Wrench Size	quantity
PN.	M	F	Φ mm	GL mm	nut/cap mm	Pcs/bag
M12M-M12F-08-SS	M12×1.5	M12×1.5	4~8	9	15/17	50
M16M-M16F-08-SS	M16×1.5	M16×1.5	4~8	9.5	20/17	50
M16M-M16F-10-SS	M16×1.5	M16×1.5	6~10	9.5	20/21	50
M20M-M20F-12-SS	M20×1.5	M20×1.5	7~12	12	24/24	50
M20M-G1/2F-12-SS	M20×1.5	G1/2	7~12	12	24/24	50
M20M-G3/4F-12-SS	M20×1.5	G3/4	7~12	12	24/31	50
M20M-NPT1/2F-12-SS	M20×1.5	NPT1/2	7~12	12	24/24	50
M20M-NPT3/4F-12-SS	M20×1.5	NPT3/4	7~12	12	24/31	50
M20M-M20F-14-SS	M20×1.5	M20×1.5	8~14	12	24/26	50
*M20M-G1/2F-14-SS	M20×1.5	G1/2	8~14	12	24/26	50
*M20M-G3/4F-14-SS	M20×1.5	G3/4	8~14	12	24/31	50
*M20M-NPT1/2F-14-SS	M20×1.5	NPT1/2	8~14	12	24/26	50
*M20M-NPT3/4F-14-SS	M20×1.5	NPT3/4	8~14	12	24/31	50
M25M-M25F-18-SS	M25×1.5	M25×1.5	13~18	12	30/31	50
M25M-G3/4-18-SS	M25×1.5	G3/4	13~18	12	30/31	50
M25M-NPT3/4F-18-SS	M25×1.5	NPT3/4	13~18	12	30/31	50
M32M-M32F-25-SS	M32×1.5	M32×1.5	18~25	12.5	38/40	20
M32M-G1F-25-SS	M32×1.5	G1	18~25	12.5	38/40	20
M32M-NPT1F-25-SS	M32×1.5	NPT1	18~25	12.5	38/40	20
M40M-M40F-31-SS	M40×1.5	M40×1.5	25~31	14	48/50	10
M40M-G1-1/4F-31-SS	M40×1.5	G1-1/4	25~31	14	48/50	10
M40M-NPT1-1/4F-31-SS	M40×1.5	NPT1-1/4	25~31	14	48/50	10
M50M-M50F-41-SS	M50×1.5	M50×1.5	33~41	15	58/60	10
M50M-G1-1/2-41-SS	M50×1.5	G1-1/2	33~41	15	58/60	10
M50M-NPT1-1/2-41-SS	M50×1.5	NPT1-1/2	33~41	15	58/60	10
M63M-M63F-44-SS	M63×1.5	M63×1.5	36~44	15	71/65	1
M63M-G2F-44-SS	M63×1.5	G2	36~44	15	71/65	1
M63M-NPT2F-44-SS	M63×1.5	NPT2	36~44	15	71/65	1

英制 G 牙/ G thread

蓝江产品型号	外螺纹	内螺纹	电缆范围	螺纹长度	扳手尺寸	包装数量
Product model	M-thread	F-thread	Cable range	Thread length	Wrench Size	quantity
PN.	G	F	Φ mm	GL mm	nut/cap mm	Pcs/bag
G1/2M-G1/2F-12-SS	G1/2	G1/2	7~12	12	24/24	50
*G1/2M-G3/4F-12-SS	G1/2	G3/4	7~12	12	24/31	50
*G1/2M-M20F-12-SS	G1/2	M20×1.5	7~12	12	24/24	50
*G1/2M-M25F-12-SS	G1/2	M25×1.5	7~12	12	24/31	50
*G1/2M-NPT1/2F-12-SS	G1/2	NPT1/2	7~12	12	24/24	50
*G1/2M-NPT3/4F-12-SS	G1/2	NPT3/4	7~12	12	24/31	50
G3/4M-G3/4F-18-SS	G3/4	G3/4	13~18	12	31/31	50
G3/4M-G1/2F-12-SS	G3/4	G1/2	7~12	12	31/24	50
*G3/4M-M25F-18-SS	G3/4	M25×1.5	13~18	12	31/31	50
*G3/4M-M20F-12-SS	G3/4	M20×1.5	7~12	12	31/24	50
*G3/4M-NPT3/4F-18-SS	G3/4	NPT3/4	13~18	12	30/31	50
*G3/4M-NPT1/2F-18-SS	G3/4	NPT1/2	7~12	12	30/24	50
G1M-G1F-25-SS	G1	G1	18~25	12.5	38/40	20
*G1M-NPT1F-25-SS	G1	NPT1	18~25	12.5	38/40	20
G1M-M32F-25-SS	G1	M32×1.5	18~25	12.5	38/40	20
G1-1/4M-G1-1/4F-31-SS	G1-1/4	G1-1/4	25~31	14	48/50	10
*G1-1/4-NPT1-1/4F-31-SS	G1-1/4	NPT1-1/4	25~31	14	48/50	10
G1-1/2M-G1-1/2-31-SS	G1-1/2	G1-1/2	25~31	15	58/50	10
*G1-1/2M-NPT1-1/2-31-SS	G1-1/2	NPT1-1/2	25~31	15	58/50	10
G2M-G2F-44-SS	G2	G2	36~44	15	71/65	1
*G2M-NPT2F-44-SS	G2	NPT2	36~44	15	71/65	1



美制 NPT 牙/ NPT thread

蓝江产品型号	外螺纹	内螺纹	电缆范围	螺纹长度	扳手尺寸	包装数量
Product model	M-thread	F-thread	Cable range	Thread length	Wrench Size	quantity
PN.	NPT	F	Φ mm	GL mm	nut/cap mm	Pcs/bag
NPT1/2M-NPT1/2F-12-SS	NPT1/2	NPT1/2	7~12	12	24/24	50
NPT1/2M-NPT3/4F-12-SS	NPT1/2	NPT3/4	7~12	12	24/31	50
NPT1/2M-M20F-12-SS	NPT1/2	M20×1.5	7~12	12	24/24	50
NPT1/2M-M25F-12-SS	NPT1/2	M25×1.5	7~12	12	24/31	50
NPT1/2M-G1/2F-12-SS	NPT1/2	G1/2	7~12	12	24/24	50
NPT1/2M-G3/4F-12-SS	NPT1/2	G3/4	7~12	12	24/31	50
NPT3/4M-NPT3/4F-18-SS	NPT3/4	NPT3/4	13~18	12	30/31	50
NPT3/4M-NPT1/2F-18-SS	NPT3/4	NPT1/2	7~12	12	30/24	50
NPT3/4M-G3/4F-18-SS	NPT3/4	G3/4	13~18	12	31/31	50
NPT3/4M-G1/2F-18-SS	NPT3/4	G1/2	7~12	12	30/24	50
NPT3/4M-M25F-18-SS	NPT3/4	M25×1.5	13~18	12	31/31	50
NPT3/4M-M20F-18-SS	NPT3/4	M20×1.5	7~12	12	30/24	50
NPT1M-NPT1F-25-SS	NPT1	NPT1	18~25	12.5	38/40	20
NPT1M-G1F-25-SS	NPT1	G1	18~25	12.5	38/40	20
NPT1M-M32F-25-SS	NPT1	M32×1.5	18~25	12.5	38/40	20
NPT1-1/4M-G1-1/4F-31-SS	NPT1-1/4	G1-1/4	25~31	14	48/50	10
NPT1-1/4-NPT1-1/4F-31-SS	NPT1-1/4	NPT1-1/4	25~31	14	48/50	10
NPT1-1/2M-G1-1/2-31-SS	NPT1-1/2	G1-1/2	25~31	15	58/50	10
NPT1-1/2M-NPT1-1/2-31-SS	NPT1-1/2	NPT1-1/2	25~31	15	58/50	10
NPT2M-G2F-44-SS	NPT2	G2	36~44	15	71/65	1
NPT2M-NPT2F-44-SS	NPT2	NPT2	36~44	15	71/65	1

