

## 防爆不锈钢填料函

- 产品材料:** 默认 304, 可选 316 及 316L, 密封件为硅胶
- 防护等级:** IP66
- 工作温度:** -20° ~ 180°
- 产品性能:** 符合 Exd 隔爆, Exe 增安及 ExtD 粉尘防爆
- 订购说明:**

- 1) 默认五件一套: O型圈, 主体, 密封件, 金属垫, 压紧帽
- 2) 特别提示, 发货不附螺母, 如需另外购买
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set)
- 4) 接受定制, 可加长螺纹, 定制锁线范围, 具体联系客服



## Explosion proof stainless steel stuffing box

- Product material:** default 304, optional 316 and 316L, and the seal is silicone
  - Protection grade:** IP66
  - Operating temperature:** - 20 °~180 °
  - Product performance:** Exd explosion-proof, Exe increased safety and ExtD dust explosion-proof
  - Ordering Instructions:**
- 1) The default is a set of five pieces: O-ring, main body, seal, metal gasket, compression cap
  - 2) Special note: nuts are not attached to the shipment, if you need to purchase separately
  - 3) The product price is (RMB: yuan/set, USD: USD/set)
  - 4) Accept customization, lengthen the thread, customize the lock range, contact customer service for details

### 产品应用/Product application



## 产品尺寸表/Product size

| 蓝江产品型号              | 螺纹规格        | 电缆范围        | 螺纹长度          | 扳手尺寸        |
|---------------------|-------------|-------------|---------------|-------------|
| Product model       | Thread size | Cable range | Thread length | Wrench Size |
| PN.                 | Metric      | φ mm        | GL mm         | cap mm      |
| Exd1-M20-14-SS      | M20×1.5     | 8~14        | 15            | 26          |
| Exd1-M25-16-SS      | M25×1.5     | 8~16        | 15            | 30          |
| Exd1-M25-20-SS      | M25×1.5     | 10~20       | 15            | 38          |
| Exd1-M32-20-SS      | M32×1.5     | 10~20       | 18            | 38          |
| Exd1-M32-25-SS      | M32×1.5     | 10~25       | 18            | 46          |
| Exd1-M40-25-SS      | M40×1.5     | 10~25       | 18            | 46          |
| Exd1-M40-32-SS      | M40×1.5     | 14~32       | 18            | 50          |
| Exd1-M50-32-SS      | M50×1.5     | 14~32       | 18            | 50          |
| Exd1-M50-41-SS      | M50×1.5     | 17~41       | 18            | 62          |
| Exd1-M63-41-SS      | M63×1.5     | 17~41       | 18            | 62          |
| Exd1-G1/2-14-SS     | G1/2        | 8~14        | 15            | 26          |
| Exd1-G3/4-16-SS     | G3/4        | 8~16        | 15            | 30          |
| Exd1-G3/4-20-SS     | G3/4        | 10~20       | 15            | 38          |
| Exd1-G1-20-SS       | G1          | 10~20       | 18            | 38          |
| Exd1-G1-25-SS       | G1          | 10~25       | 18            | 46          |
| Exd1-G1-1/4-25-SS   | G1-1/4      | 10~25       | 18            | 46          |
| Exd1-G1-1/4-32-SS   | G1-1/4      | 14~32       | 18            | 50          |
| Exd1-G1-1/2-32-SS   | G1-1/2      | 14~32       | 18            | 50          |
| Exd1-G1-1/2-41-SS   | G1-1/2      | 17~41       | 18            | 62          |
| Exd1-G2-41-SS       | G2          | 17~41       | 18            | 62          |
| Exd1-NPT1/2-14-SS   | NPT1/2      | 8~14        | 15            | 26          |
| Exd1-NPT3/4-16-SS   | NPT3/4      | 8~16        | 15            | 30          |
| Exd1-NPT3/4-20-SS   | NPT3/4      | 10~20       | 15            | 38          |
| Exd1-NPT1-20-SS     | NPT1        | 10~20       | 18            | 38          |
| Exd1-NPT1-25-SS     | NPT1        | 10~25       | 18            | 46          |
| Exd1-NPT1-1/4-25-SS | NPT1-1/4    | 10~25       | 18            | 46          |
| Exd1-NPT1-1/4-32-SS | NPT1-1/4    | 14~32       | 18            | 50          |
| Exd1-NPT1-1/2-32-SS | NPT1-1/2    | 14~32       | 18            | 50          |
| Exd1-NPT1-1/2-41-SS | NPT1-1/2    | 17~41       | 18            | 62          |
| Exd1-NPT2-41-SS     | NPT2        | 17~41       | 18            | 62          |