

防爆型黄铜镀镍电缆防水接头

•**产品材料:** 黄铜镀镍, 密封件 EPDM, 夹紧爪尼龙

•**防护等级:** IP68

•**工作温度:** 常规-40° ~ 105°, 短时可达 120°

•**阻燃等级:** UL94V-2, 可定制 V0 级阻燃

•**防爆等级:** Exe IIC Gb/Ex tD A20 IP68

•**订购说明:**

- 1) 默认五件套: 垫片, 主体, 夹紧爪, 密封圈, 螺帽;
- 2) 特殊说明, 发货不附螺母, 如需另外购买;
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set)



Explosion proof nickel plated brass cable gland

•**Product material:** brass nickel plating, seal EPDM, clamping claw nylon

•**Protection grade:** IP68

•**Working temperature:** normal - 40 °~105 °, short-term up to 120 °

•**Flame retardant grade:** UL94V-2, customized V0 flame retardant

•**Explosion proof grade:** Exe IIC Gb/Ex tD A20 IP68

•**Ordering Instructions:**

- 1) Default five piece set: gasket, main body, clamping claw, sealing ring, nut;
- 2) Special instructions, nuts are not attached to the shipment, if necessary, purchase separately;
- 3) The product price is (RMB: yuan/set, USD: USD/set)

•**产品应用/Product application**



公制螺纹/Metric thread

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	M Thread	Cable range	Thread length	Wrench Size
PN.	M	φ mm	GL mm	cap mm
MG12A-08	M12×1.5	4~8	8	17/17
MG12A-05	M12×1.5	3~5	8	17/17
MG16AS-08	M16×1.5	4~8	8	18/18
MG16A-10	M16×1.5	6~10	9	22/22
MG16A-07	M16×1.5	4~7	9	22/22
MG18A-10	M18×1.5	6~10	9	22/22
MG18A-07	M18×1.5	4~7	9	22/22
MG18A-14	M18×1.5	8~14	9.5	26/26
MG20AS-12	M20×1.5	7~12	10	24/24
MG20AS-11	M20×1.5	6~11	10	24/24
MG20AS-09	M20×1.5	5~9	10	24/24
MG20A-14	M20×1.5	8~14	10	26/26
MG22A-14	M22×1.5	8~14	10	26/26
MG25A-18	M25×1.5	13~18	12	32/32
MG25A-16	M25×1.5	11~16	12	32/32
MG25A-14	M25×1.5	8~14	12	32/32
MG25A-10	M25×1.5	6~10	12	32/32
MG32A-25	M32×1.5	18~25	12.5	40/40
MG32A-22	M32×1.5	16~22	12.5	40/40
MG40A-30	M40×1.5	24~30	15	50/50
MG40A-25	M40×1.5	18~25	15	50/50
MG50A-40	M50×1.5	33~40	15	59/59
MG50A-33	M50×1.5	25~33	15	59/59
MG63A-45	M63×1.5	38~45	15	68/68

德制 PG 螺纹/PG thread

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	PG Thread	Cable range	Thread length	Wrench Size
PN.	PG	φ mm	GL mm	cap mm
PG7A-08	PG7	4 ~ 8	8	17/17
PG7A-05	PG7	3 ~ 5	8	17/17
PG9A-08	PPG9	4 ~ 8	8	18/18
PG9A-05	PG9	3 ~ 5	8	18/18
PG11A-10	PG11	6 ~ 10	9	22/22
PG11A-07	PG11	4 ~ 7	9	22/22
PG13.5A-12	PG13.5	7 ~ 12	9.5	24/24
PG13.5A-09	PG13.5	5 ~ 9	9.5	24/24
PG16A-14	PG16	8 ~ 14	10	26/26
PG16A-12	PG16	6 ~ 12	10	26/26
PG21A-18	PG21	13 ~ 18	12	32/32
PG21A-16	PG21	11 ~ 16	12	32/32
PG21A-14	PG21	8 ~ 14	12	32/32
PG21A-10	PG21	6 ~ 10	12	32/32
PG29A-25	PG29	18 ~ 25	12.5	40/40
PG29A-22	PG29	16 ~ 22	12.5	40/40
PG36A-30	PG36	24 ~ 30	15	50/50
PG36A-25	PG36	18 ~ 25	15	50/50
PG42A-40	PG42	33 ~ 40	15	59/59
PG42A-33	PG42	25 ~ 33	15	59/59
PG48A-45	PG48	38 ~ 45	15	68/68

英制 G 螺纹/G thread

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	G Thread	Cable range	Thread length	Wrench Size
PN.	G	φ mm	GL mm	cap mm
G1/4A-08	G1/4	4~8	8	17/17
G1/4A-05	G1/4	3~5	8	17/17
G3/8A-10	G3/8	6~10	9	22/22
G3/8A-07	G3/8	4~7	9	22/22
G1/2A-12	G1/2	7~12	9.5	24/24
G1/2A-09	G1/2	5~9	9.5	24/24
G1/2A-14	G1/2	8~14	10	26/26
G1/2A-12	G1/2	6~12	10	26/26
G3/4A-18	G3/4	13~18	12	32/32
G3/4A-16	G3/4	11~16	12	32/32
G3/4A-14	G3/4	8~14	12	32/32
G3/4A-10	G3/4	6~10	12	32/32
G1A-25	G1	18~25	12.5	40/40
G1A-22	G1	16~22	12.5	40/40
G1-1/4A-30	G1-1/4	24~30	15	50/50
G1-1/4A-25	G1-1/4	18~25	15	50/50
G1-1/2A-40	G1-1/2	33~40	15	59/59
G1-1/2A-33	G1-1/2	25~33	15	59/59
G2A-45	G2	38~45	15	68/68

美制 NPT 螺纹/NPT thread

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	NPT Thread	Cable ranNPTe	Thread lenNPTth	Wrench Size
PN.	NPT	φ mm	NPTL mm	cap mm
NPT1/4A-08	NPT1/4	4~8	8	17/17
NPT1/4A-05	NPT1/4	3~5	8	17/17
NPT3/8A-10	NPT3/8	6~10	9	22/22
NPT3/8A-07	NPT3/8	4~7	9	22/22
NPT1/2A-12	NPT1/2	7~12	9.5	24/24
NPT1/2A-09	NPT1/2	5~9	9.5	24/24
NPT1/2A-14	NPT1/2	8~14	10	26/26
NPT1/2A-12	NPT1/2	6~12	10	26/26
NPT3/4A-18	NPT3/4	13~18	12	32/32
NPT3/4A-16	NPT3/4	11~16	12	32/32
NPT3/4A-14	NPT3/4	8~14	12	32/32
NPT3/4A-10	NPT3/4	6~10	12	32/32
NPT1A-25	NPT1	18~25	12.5	40/40
NPT1A-22	NPT1	16~22	12.5	40/40
NPT1-1/4A-30	NPT1-1/4	24~30	15	50/50
NPT1-1/4A-25	NPT1-1/4	18~25	15	50/50
NPT1-1/2A-40	NPT1-1/2	33~40	15	59/59
NPT1-1/2A-33	NPT1-1/2	25~33	15	59/59
NPT2A-45	NPT2	38~45	15	68/68