

## A 型-EMC 黄铜镀镍电缆防水接头

- 产品材料:** 黄铜镀镍, 密封件 EPDM, 夹紧爪尼龙
- 防护等级:** IP68
- 工作温度:** 常规-40° ~ 105°, 短时可达 120°
- 阻燃等级:** UL94V-2, 可定制 V0 级阻燃
- 产品特性:** 可有效屏蔽电磁干扰, 保障设备正常运转

### •订购说明:

- 1) 默认六件套: 垫片,主体,防磁波片,夹紧爪,密封圈,螺帽;
- 2) 特殊说明, 发货不附螺母, 如需另外购买;
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set)



## Type A - EMC brass nickel plated cable gland

- Product material:** brass nickel plating, seal EPDM, clamping claw nylon
- Protection grade:** IP68
- Working temperature:** normal - 40 °~105 °, short-term up to 120 °
- Flame retardant grade:** UL94V-2, customized V0 flame retardant
- Product characteristics:** it can effectively shield electromagnetic interference and ensure normal operation of equipment
- Ordering Instructions:**
  - 1) Default six piece set: gasket, main body, antimagnetic wave plate, clamping claw, sealing ring, nut;
  - 2) Special instructions, nuts are not attached to the shipment, if necessary, purchase separately;
  - 3) The product price is (RMB: yuan/set, USD: USD/set)



## 公制螺纹尺寸/ Metric thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	M Thread	Cable range	Thread length	Wrench Size
PN.	M	φ mm	GL mm	cap mm
EMC-MG12A-08	M12×1.5	4~8	8	17/17
EMC-MG12A-05	M12×1.5	3~5	8	17/17
EMC-MG16AS-08	M16×1.5	4~8	8	18/18
EMC-MG16A-10	M16×1.5	6~10	9	22/22
EMC-MG16A-07	M16×1.5	4~7	9	22/22
EMC-MG18A-10	M18×1.5	6~10	9	22/22
EMC-MG18A-07	M18×1.5	4~7	9	22/22
EMC-MG18A-14	M18×1.5	8~14	9.5	26/26
EMC-MG20AS-12	M20×1.5	7~12	10	24/24
EMC-MG20AS-11	M20×1.5	6~11	10	24/24
EMC-MG20AS-09	M20×1.5	5~9	10	24/24
EMC-MG20A-14	M20×1.5	8~14	10	26/26
EMC-MG22A-14	M22×1.5	8~14	10	26/26
EMC-MG25A-18	M25×1.5	13~18	12	32/32
EMC-MG25A-16	M25×1.5	11~16	12	32/32
EMC-MG25A-14	M25×1.5	8~14	12	32/32
EMC-MG25A-10	M25×1.5	6~10	12	32/32
EMC-MG32A-25	M32×1.5	18~25	12.5	40/40
EMC-MG32A-22	M32×1.5	16~22	12.5	40/40
EMC-MG40A-30	M40×1.5	24~30	15	50/50
EMC-MG40A-25	M40×1.5	18~25	15	50/50
EMC-MG50A-40	M50×1.5	33~40	15	59/59
EMC-MG50A-33	M50×1.5	25~33	15	59/59
EMC-MG63A-45	M63×1.5	38~45	15	68/68

## 德制 PG 螺纹尺寸/ PG thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	PG Thread	Cable range	Thread length	Wrench Size
PN.	PG	φ mm	GL mm	cap mm
EMC-PG7A-08	PG7	4 ~ 8	8	17/17
EMC-PG7A-05	PG7	3 ~ 5	8	17/17
EMC-PG9A-08	PPG9	4 ~ 8	8	18/18
EMC-PG9A-05	PG9	3 ~ 5	8	18/18
EMC-PG11A-10	PG11	6 ~ 10	9	22/22
EMC-PG11A-07	PG11	4 ~ 7	9	22/22
EMC-PG13.5A-12	PG13.5	7 ~ 12	9.5	24/24
EMC-PG13.5A-09	PG13.5	5 ~ 9	9.5	24/24
EMC-PG16A-14	PG16	8 ~ 14	10	26/26
EMC-PG16A-12	PG16	6 ~ 12	10	26/26
EMC-PG21A-18	PG21	13 ~ 18	12	32/32
EMC-PG21A-16	PG21	11 ~ 16	12	32/32
EMC-PG21A-14	PG21	8 ~ 14	12	32/32
EMC-PG21A-10	PG21	6 ~ 10	12	32/32
EMC-PG29A-25	PG29	18 ~ 25	12.5	40/40
EMC-PG29A-22	PG29	16 ~ 22	12.5	40/40
EMC-PG36A-30	PG36	24 ~ 30	15	50/50
EMC-PG36A-25	PG36	18 ~ 25	15	50/50
EMC-PG42A-40	PG42	33 ~ 40	15	59/59
EMC-PG42A-33	PG42	25 ~ 33	15	59/59
EMC-PG48A-45	PG48	38 ~ 45	15	68/68

## 英制 G 螺纹尺寸/ G thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	G Thread	Cable range	Thread length	Wrench Size
PN.	G	φ mm	GL mm	cap mm
EMC-G1/4A-08	G1/4	4~8	8	17/17
EMC-G1/4A-05	G1/4	3~5	8	17/17
EMC-G3/8A-10	G3/8	6~10	9	22/22
EMC-G3/8A-07	G3/8	4~7	9	22/22
EMC-G1/2A-12	G1/2	7~12	9.5	24/24
EMC-G1/2A-09	G1/2	5~9	9.5	24/24
EMC-G1/2A-14	G1/2	8~14	10	26/26
EMC-G1/2A-12	G1/2	6~12	10	26/26
EMC-G3/4A-18	G3/4	13~18	12	32/32
EMC-G3/4A-16	G3/4	11~16	12	32/32
EMC-G3/4A-14	G3/4	8~14	12	32/32
EMC-G3/4A-10	G3/4	6~10	12	32/32
EMC-G1A-25	G1	18~25	12.5	40/40
EMC-G1A-22	G1	16~22	12.5	40/40
EMC-G1-1/4A-30	G1-1/4	24~30	15	50/50
EMC-G1-1/4A-25	G1-1/4	18~25	15	50/50
EMC-G1-1/2A-40	G1-1/2	33~40	15	59/59
EMC-G1-1/2A-33	G1-1/2	25~33	15	59/59
EMC-G2A-45	G2	38~45	15	68/68

## 美制 NPT 螺纹尺寸/ NPT thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	NPT Thread	Cable range	Thread length	Wrench Size
PN.	NPT	φ mm	GL mm	cap mm
EMC-NPT1/4A-08	NPT1/4	4~8	8	17/17
EMC-NPT1/4A-05	NPT1/4	3~5	8	17/17
EMC-NPT3/8A-10	NPT3/8	6~10	9	22/22
EMC-NPT3/8A-07	NPT3/8	4~7	9	22/22
EMC-NPT1/2A-12	NPT1/2	7~12	9.5	24/24
EMC-NPT1/2A-09	NPT1/2	5~9	9.5	24/24
EMC-NPT1/2A-14	NPT1/2	8~14	10	26/26
EMC-NPT1/2A-12	NPT1/2	6~12	10	26/26
EMC-NPT3/4A-18	NPT3/4	13~18	12	32/32
EMC-NPT3/4A-16	NPT3/4	11~16	12	32/32
EMC-NPT3/4A-14	NPT3/4	8~14	12	32/32
EMC-NPT3/4A-10	NPT3/4	6~10	12	32/32
EMC-NPT1A-25	NPT1	18~25	12.5	40/40
EMC-NPT1A-22	NPT1	16~22	12.5	40/40
EMC-NPT1-1/4A-30	NPT1-1/4	24~30	15	50/50
EMC-NPT1-1/4A-25	NPT1-1/4	18~25	15	50/50
EMC-NPT1-1/2A-40	NPT1-1/2	33~40	15	59/59
EMC-NPT1-1/2A-33	NPT1-1/2	25~33	15	59/59
EMC-NPT2A-45	NPT2	38~45	15	68/68

## B 型-EMC 黄铜镀镍电缆防水接头

- 产品材料:** 黄铜镀镍, 密封件硅胶, 夹紧爪尼龙
- 防护等级:** IP68
- 工作温度:** 常规-40° ~ 105°, 短时可达 120°
- 阻燃等级:** UL94V-2, 可定制 V0 级阻燃
- 产品特性:** 可有效屏蔽电磁干扰, 保障设备正常运转



### •订购说明:

- 1) 默认六件套: 垫片,主体,防磁波片,夹紧爪,密封圈,螺帽;
- 2) 特殊说明, 发货不附螺母, 如需另外购买;
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set)

## Type B - EMC brass nickel plated cable gland

- Product material:** brass nickel plating, seal EPDM, clamping claw nylon
- Protection grade:** IP68
- Working temperature:** normal - 40 °~105 °, short-term up to 120 °
- Flame retardant grade:** UL94V-2, customized V0 flame retardant
- Product characteristics:** it can effectively shield electromagnetic interference and ensure normal operation of equipment

### •Ordering Instructions:

- 1) Default six piece set: gasket, main body, antimagnetic wave plate, clamping claw, sealing ring, nut;
- 2) Special instructions, nuts are not attached to the shipment, if necessary, purchase separately;
- 3) The product price is (RMB: yuan/set, USD: USD/set)



## 公制螺纹尺寸/ Metric thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	M Thread	Cable range	Thread length	Wrench Size
PN.	M	φ mm	GL mm	SW1/SW2
EMC-MG12B-08	M12×1.5	4~8	6	14/16
EMC-MG16B-08	M16×1.5	4~8	7	17/18
EMC-MG16B-10	M16×1.5	5~10	7	20/20
EMC-MG18B-10	M18×1.5	5~10	7	20/20
EMC-MG20B-12	M20×1.5	6~12	7	22/22
EMC-MG20B-14	M20×1.5	8~14	7	24/24
EMC-MG22B-14	M22×1.5	8~14	8	24/24
EMC-MG24B-14	M24×1.5	8~14	8	24/27
EMC-MG25B-14	M25×1.5	8~14	8	24/27
EMC-MG25B-16	M25×1.5	10~16	8	27/27
EMC-MG25B-18	M25×1.5	13~18	8	30/30
EMC-MG27B-18	M27×2.0	13~18	8	30/30
EMC-MG30B-18	M30×2.0	13~18	8	30/32
EMC-MG32B-22	M32×1.5	15~22	9	34/34
EMC-MG32B-25	M32×1.5	18~25	9	40/40
EMC-MG36B-25	M36×2.0	18~25	9	40/40
EMC-MG40B-25	M40×1.5	18~25	9	40/43
EMC-MG40B-28	M40×1.5	20~28	10	43/43
EMC-MG40B-30	M40×1.5	22~30	10	45/45
EMC-MG40B-32	M40×1.5	24~32	10	50/50
EMC-MG50B-32	M50×1.5	24~32	12	57/55
EMC-MG50B-38	M50×1.5	30~38	12	57/55
EMC-MG60B-44	M60×2.0	37~44	12	64/64
EMC-MG63B-44	M63×1.5	37~44	12	64/68

## 德制 PG 螺纹尺寸/ PG thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	M Thread	Cable range	Thread length	Wrench Size
PN.	PG	φ mm	GL mm	S1/S2 mm
EMC-PG7B-06	PG7	3 ~ 6.5	6	14/14
EMC-PG9B-08	PG9	4 ~ 8	7	17/17
EMC-PG9B-10	PG9	5 ~ 10	7	20/20
EMC-PG11B-10	PG11	5 ~ 10	7	20/20
EMC-PG13.5B-08	PG13.5	4 ~ 8	7	17/22
EMC-PG13.5B-10	PG13.5	5 ~ 10	7	20/22
EMC-PG13.5B-12	PG13.5	6 ~ 12	7	22/22
EMC-PG13.5B-14	PG13.5	8 ~ 14	7	24/24
EMC-PG16B-12	PG16	6 ~ 12	8	22/24
EMC-PG16B-14	PG16	8 ~ 14	8	24/24
EMC-PG19B-14	PG19	8 ~ 14	8	24/27
EMC-PG21B-16	PG21	10 ~ 16	8	27/30
EMC-PG21B-18	PG21	13 ~ 18	8	30/30
EMC-PG25B-20	PG25	15 ~ 20	8	30/32
EMC-PG29B-25	PG29	18 ~ 25	9	40/40
EMC-PG36B-25	PG36	18 ~ 25	10	40/50
EMC-PG36B-32	PG36	24 ~ 32	10	50/50
EMC-PG42B-38	PG42	30 ~ 38	10	58/58
EMC-PG48B-44	PG48	37 ~ 44	12	64/64



## 英制 G 螺纹尺寸/ G thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	M Thread	Cable range	Thread length	Wrench Size
PN.	G	φ mm	GL mm	S1/S2 mm
EMC-G1/4B-06	G1/4	3 ~ 6.5	6	14/16
EMC-G3/8B-08	G3/8	4 ~ 8	7	17/18
EMC-G1/2B-10	G1/2	5 ~ 10	8	20/22
EMC-G1/2B-12	G1/2	6 ~ 12	8	22/22
EMC-G1/2B-14	G1/2	8 ~ 14	8	24/24
EMC-G3/4B-18	G3/4	13 ~ 18	8	30/30
EMC-G1B-22	G1	16 ~ 22	9	34/36
EMC-G1B-25	G1	18 ~ 25	9	40/40
EMC-G1-1/4B-28	G1-1/4	22 ~ 28	10	43/45
EMC-G1-1/4B-30	G1-1/4	23 ~ 30	10	45/45
EMC-G1-1/2B-32	G1-1/2	25 ~ 32	10	50/52
EMC-G2B-44	G2	37 ~ 44	12	64/64
EMC-G2-1/2B-52	G2-1/2	42 ~ 52	15	76/81
EMC-G3B-70	G3	65 ~ 70	18	98/98

## 美制 NPT 螺纹尺寸/ NPT thread size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	M Thread	Cable range	Thread length	Wrench Size
PN.	NPT	φ mm	GL mm	S1/S2 mm
EMC-NPT1/4B-06	NPT1/4	3 ~ 6.5	6	14/16
EMC-NPT3/8B-08	NPT3/8	4 ~ 8	7	17/18
EMC-NPT1/2B-10	NPT1/2	5 ~ 10	8	20/22
EMC-NPT1/2B-12	NPT1/2	6 ~ 12	8	22/22
EMC-NPT1/2B-14	NPT1/2	8 ~ 14	8	24/24
EMC-NPT3/4B-18	NPT3/4	13 ~ 18	8	30/30
EMC-NPT1B-22	NPT1	16 ~ 22	9	34/36
EMC-NPT1B-25	NPT1	18 ~ 25	9	40/40
EMC-NPT1-1/4B-28	NPT1-1/4	22 ~ 28	10	43/45
EMC-NPT1-1/4B-30	NPT1-1/4	23 ~ 30	10	45/45
EMC-NPT1-1/2B-32	NPT1-1/2	25 ~ 32	10	50/52
EMC-NPT2B-44	NPT2	37 ~ 44	12	64/64
EMC-NPT2-1/2B-52	NPT2-1/2	42 ~ 52	15	76/81
EMC-NPT3B-70	NPT3	65 ~ 70	18	98/98

## T 型-EMC 弹片式金属电缆防水接头

- 产品材料:** 黄铜镀镍, 密封件硅胶, 夹紧爪尼龙
- 防护等级:** IP68
- 工作温度:** 常规-40° ~ 105°, 短时可达 120°
- 阻燃等级:** UL94V-2, 可定制 V0 级阻燃
- 产品特性:** 可有效屏蔽电磁干扰, 保障设备正常运转

### •订购说明:

- 1) 默认六件套: 垫片,主体,防磁波片,夹紧爪,密封圈,螺帽;
- 2) 特殊说明, 发货不附螺母, 如需另外购买;
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set)



## Type T - EMC brass nickel plated cable gland

- Product material:** brass nickel plating, seal EPDM, clamping claw nylon
- Protection grade:** IP68
- Working temperature:** normal - 40 °~105 °, short-term up to 120 °
- Flame retardant grade:** UL94V-2, customized V0 flame retardant
- Product characteristics:** it can effectively shield electromagnetic interference and ensure normal operation of equipment

### •Ordering Instructions:

- 1) Default six piece set: gasket, main body, antimagnetic wave plate, clamping claw, sealing ring, nut;
- 2) Special instructions, nuts are not attached to the shipment, if necessary, purchase separately;
- 3) The product price is (RMB: yuan/set, USD: USD/set)



## 产品尺寸表/Product size table

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	M Thread	Cable range	Thread length	Wrench Size
PN.	M	φ mm	GL mm	SW1/SW2
TEMC-M16-08	M16×1.5	4~8	7	17/18
TEMC-M16-10	M16×1.5	5~10	7	20/20
TEMC-M18-10	M18×1.5	5~10	7	20/20
TEMC-M20-12	M20×1.5	6~12	7	22/22
TEMC-M20-14	M20×1.5	8~14	7	24/24
TEMC-M25-16	M25×1.5	10~16	8	27/27
TEMC-M25-18	M25×1.5	13~18	8	30/30
TEMC-M32-22	M32×1.5	15~22	9	34/34
TEMC-M32-25	M32×1.5	18~25	9	40/40

# H 型-EMC 新能源金属电缆防水接头

- 产品材料:** 黄铜镀镍, 密封件硅胶
- 防护等级:** IP68
- 工作温度:** 常规-40° ~ 105°, 短时可达 120°
- 阻燃等级:** UL94V-2, 可定制 V0 级阻燃
- 产品特性:** 可有效屏蔽电磁干扰, 保障设备正常运转

## •订购说明:

- 1) 默认五件套: 垫片,主体,防磁波片,密封圈,螺帽;
- 2) 特殊说明, 发货不附螺母, 如需另外购买;
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set)



# Type H- EMC new energy metal cable gland

- Product material:** brass nickel plating, silica gel
- Protection grade:** IP68
- Working temperature:** normal - 40 °~105 °, short-term up to 120 °
- Flame retardant grade:** UL94V-2, customized V0 flame retardant
- Product characteristics:** it can effectively shield electromagnetic interference and ensure normal operation of equipment
- Ordering Instructions:**
  - 1) Default six piece set: gasket, main body, antimagnetic wave plate, clamping claw, sealing ring, nut;
  - 2) Special instructions, nuts are not attached to the shipment, if necessary, purchase separately;
  - 3) The product price is (RMB: yuan/set, USD: USD/set)



## 产品尺寸表/Product size table

蓝江产品型号	螺纹规格	电缆范围	螺纹长度	扳手尺寸
Product model	M Thread	Cable range	Thread length	Wrench Size
PN.	M	φ mm	GL mm	SW1/SW2
HEMC-MG20B-14	M20×1.5	8 ~ 14	7	24/24
HEMC-MG25B-18	M25×1.5	13 ~ 18	9	30/30
HEMC-MG32B-24	M32×1.5	18 ~ 24	11	36/36
HEMC-MG40B-35	M40×1.5	28 ~ 35	11	50/46
HEMC-MG50B-38	M50×1.5	30 ~ 38	12	57/55
HEMC-MG63B-44	M63×1.5	37 ~ 44	12	64/68