

双锁紧金属电缆防水接头

•**产品材料:** 黄铜镀镍, 密封件 EPDM, 夹紧爪尼龙

•**防护等级:** IP68

•**工作温度:** 常规-40° ~ 105°, 短时可达 120°

•**阻燃等级:** UL94V-2, 可定制 V0 级阻燃

•**产品特性:** 双层锁紧, 抗拉力强。

•**订购说明:**

- 1) 默认五件套: O 型圈, 主体, 夹紧爪, 密封圈, 螺帽;
- 2) 特殊说明, 发货不附螺母, 如需另外购买;
- 3) 产品价格为 (人民币: 元/套, 美元: USD/set)



Double locking metal cable waterproof joint

•**Product material:** brass nickel plating, seal EPDM, clamping claw nylon

•**Protection grade:** IP68

•**Working temperature:** normal - 40 °~105 °, short-term up to 120 °

•**Flame retardant grade:** UL94V-2, customized V0 flame retardant

•**Product features:** double locking, strong tension resistance.

•**Ordering Instructions:**

- 1) Default five piece set: O-ring, main body, clamping claw, sealing ring, nut;
- 2) Special instructions, nuts are not attached to the shipment, if necessary, purchase separately;
- 3) The product price is (RMB: yuan/set, USD: USD/set)

•**产品应用/Product application**



公制尺寸表/Metric size

| 蓝江产品型号 | 螺纹规格 | 电缆范围 | 螺纹长度 | 扳手尺寸 |
|---------------|----------|-------------|---------------|-------------|
| Product model | M Thread | Cable range | Thread length | Wrench Size |
| PN. | M | φ mm | GL mm | SW1/SW2 |
| SJ-M12B-08 | M14×1.5 | 4~8 | 6 | 14/16 |
| SJ-M16B-08 | M16×1.5 | 4~8 | 7 | 17/18 |
| SJ-M16B-10 | M16×1.5 | 5~10 | 7 | 20/20 |
| SJ-M18B-10 | M18×1.5 | 5~10 | 7 | 20/20 |
| SJ-M20B-08 | M20×1.5 | 4~8 | 7 | 17/22 |
| SJ-M20B-10 | M20×1.5 | 5~10 | 7 | 20/22 |
| SJ-M20B-12 | M20×1.5 | 6~12 | 7 | 22/22 |
| SJ-M20B-14 | M20×1.5 | 8~14 | 7 | 24/24 |
| SJ-M22B-14 | M22×1.5 | 8~14 | 8 | 24/24 |
| SJ-M24B-14 | M24×1.5 | 8~14 | 8 | 24/27 |
| SJ-M25B-14 | M25×1.5 | 8~14 | 8 | 24/27 |
| SJ-M25B-18 | M25×1.5 | 13~18 | 8 | 30/30 |
| SJ-M27B-18 | M27×2.0 | 13~18 | 8 | 30/30 |
| SJ-M30B-18 | M30×2.0 | 13~18 | 8 | 30/32 |
| SJ-M32B-22 | M32×1.5 | 15~22 | 9 | 34/34 |
| SJ-M32B-25 | M32×1.5 | 18~25 | 9 | 40/40 |
| SJ-M36B-25 | M36×2.0 | 18~25 | 9 | 40/40 |
| SJ-M40B-25 | M40×1.5 | 18~25 | 9 | 40/43 |
| SJ-M40B-30 | M40×1.5 | 22~30 | 10 | 45/45 |
| SJ-M40B-32 | M40×1.5 | 24~32 | 10 | 50/50 |
| SJ-M42B-28 | M42×2.0 | 20~28 | 10 | 50/50 |
| SJ-M48B-32 | M48×2.0 | 24~32 | 10 | 50/52 |
| SJ-M50B-32 | M50×1.5 | 24~32 | 12 | 57/55 |
| SJ-M50B-38 | M50×1.5 | 30~38 | 12 | 57/55 |
| SJ-M60B-44 | M60×2.0 | 37~44 | 12 | 64/64 |
| SJ-M63B-44 | M63×1.5 | 37~44 | 12 | 64/68 |

德制 PG 尺寸表/PG size

| 蓝江产品型号 | 螺纹规格 | 电缆范围 | 螺纹长度 | 扳手尺寸 |
|---------------|----------|-------------|---------------|-------------|
| Product model | M Thread | Cable range | Thread length | Wrench Size |
| PN. | PG | φ mm | GL mm | S1/S2 mm |
| SJ-PG7B-06 | PG7 | 3 ~ 6.5 | 6 | 14/14 |
| SJ-PG9B-08 | PG9 | 4 ~ 8 | 7 | 17/17 |
| SJ-PG9B-10 | PG9 | 5 ~ 10 | 7 | 20/20 |
| SJ-PG11B-10 | PG11 | 5 ~ 10 | 7 | 20/20 |
| SJ-PG13.5B-08 | PG13.5 | 4 ~ 8 | 7 | 17/22 |
| SJ-PG13.5B-10 | PG13.5 | 5 ~ 10 | 7 | 20/22 |
| SJ-PG13.5B-12 | PG13.5 | 6 ~ 12 | 7 | 22/22 |
| SJ-PG13.5B-14 | PG13.5 | 8 ~ 14 | 7 | 24/24 |
| SJ-PG16B-12 | PG16 | 6 ~ 12 | 8 | 22/24 |
| SJ-PG16B-14 | PG16 | 8 ~ 14 | 8 | 24/24 |
| SJ-PG19B-14 | PG19 | 8 ~ 14 | 8 | 24/27 |
| SJ-PG21B-16 | PG21 | 10 ~ 16 | 8 | 27/30 |
| SJ-PG21B-18 | PG21 | 13 ~ 18 | 8 | 30/30 |
| SJ-PG25B-20 | PG25 | 15 ~ 20 | 8 | 30/32 |
| SJ-PG29B-25 | PG29 | 18 ~ 25 | 9 | 40/40 |
| SJ-PG36B-25 | PG36 | 18 ~ 25 | 10 | 40/50 |
| SJ-PG36B-32 | PG36 | 24 ~ 32 | 10 | 50/50 |
| SJ-PG42B-38 | PG42 | 30 ~ 38 | 10 | 58/58 |
| SJ-PG48B-44 | PG48 | 37 ~ 44 | 12 | 64/64 |

英制 G 尺寸表/G size

| 蓝江产品型号 | 螺纹规格 | 电缆范围 | 螺纹长度 | 扳手尺寸 |
|-----------------|----------|-------------|---------------|-------------|
| Product model | M Thread | Cable range | Thread length | Wrench Size |
| PN. | G | φ mm | GL mm | S1/S2 mm |
| SJ-G1/4B-06 | G1/4 | 3 ~ 6.5 | 6 | 14/16 |
| SJ-G3/8B-08 | G3/8 | 4 ~ 8 | 7 | 17/18 |
| SJ-G1/2B-10 | G1/2 | 5 ~ 10 | 8 | 20/22 |
| SJ-G1/2B-12 | G1/2 | 6 ~ 12 | 8 | 22/22 |
| SJ-G1/2B-14 | G1/2 | 8 ~ 14 | 8 | 24/24 |
| SJ-G3/4B-18 | G3/4 | 13 ~ 18 | 8 | 30/30 |
| SJ-G1B-22 | G1 | 16 ~ 22 | 9 | 34/36 |
| SJ-G1B-25 | G1 | 18 ~ 25 | 9 | 40/40 |
| SJ-G1-1/4B-28 | G1-1/4 | 22 ~ 28 | 10 | 43/45 |
| SJ-G1-1/4B-30 | G1-1/4 | 23 ~ 30 | 10 | 45/45 |
| SJ-G1-1/2B-32 | G1-1/2 | 25 ~ 32 | 10 | 50/52 |
| SJ-G2B-44 | G2 | 37 ~ 44 | 12 | 64/64 |
| SJ-G2-1/2B-52 | G2-1/2 | 42 ~ 52 | 15 | 76/81 |
| SJ-NPT1/4B-06 | NPT1/4 | 3 ~ 6.5 | 6 | 14/16 |
| SJ-NPT3/8B-08 | NPT3/8 | 4 ~ 8 | 7 | 17/18 |
| SJ-NPT1/2B-10 | NPT1/2 | 5 ~ 10 | 8 | 20/22 |
| SJ-NPT1/2B-12 | NPT1/2 | 6 ~ 12 | 8 | 22/22 |
| SJ-NPT1/2B-14 | NPT1/2 | 8 ~ 14 | 8 | 24/24 |
| SJ-NPT3/4B-18 | NPT3/4 | 13 ~ 18 | 8 | 30/30 |
| SJ-NPT1B-22 | NPT1 | 16 ~ 22 | 9 | 34/36 |
| SJ-NPT1B-25 | NPT1 | 18 ~ 25 | 9 | 40/40 |
| SJ-NPT1-1/4B-28 | NPT1-1/4 | 22 ~ 28 | 10 | 43/45 |
| SJ-NPT1-1/4B-30 | NPT1-1/4 | 23 ~ 30 | 10 | 45/45 |
| SJ-NPT1-1/2B-32 | NPT1-1/2 | 25 ~ 32 | 10 | 50/52 |
| SJ-NPT2B-44 | NPT2 | 37 ~ 44 | 12 | 64/64 |
| SJ-NPT2-1/2B-52 | NPT2-1/2 | 42 ~ 52 | 15 | 76/81 |