

铠装防爆金属填料函

- 产品材料:** 黄铜, 硅胶
- 防护等级:** IP66
- 工作温度:** 常规-20° ~ 105°, 短时可达 120°
- 产品特性:** Exd IIC Gb/Exe IIC Gb/Ex tD A20 IP66。
- 产品类别:** 单密封和双密封。

•订购说明:

- 1) 特殊说明, 发货不附螺母, 如需另外购买;
- 2) 产品价格为 (人民币: 元/套, 美元: USD/set)



Armored explosion-proof metal stuffing box

- Product material:** brass, silica gel
- Protection grade:** IP66
- Working temperature:** normal - 20 °~105 °, up to 120 ° in a short time
- Product features:** Exd IIC Gb/Exe IIC Gb/Ex tD A20 IP66.
- Ordering Instructions:**

- 1) Special instructions, nuts are not attached to the shipment, if necessary, purchase separately;
- 2) The product price is (RMB: yuan/set, USD: USD/set)

•产品应用/Product application



单密封产品尺寸表/Single seal Product size

蓝江产品型号	螺纹规格/Thread size			电缆范围/Cable range		螺纹长度
				带铠电缆	内部电缆	
Product model	公制牙 M	英制牙 G	美制牙 NPT	Armored cable	Internal cable	Thread L
PN.	Metric	G(PF)	NPT	φ mm	AG mm	GL mm
DEX2-M20-16	M20×1.5	G1/2	NPT1/2	12 ~ 16	6 ~ 10	15
DEX2-M20-20	M20×1.5	G1/2	NPT1/2	15 ~ 20	11 ~ 15	15
DEX2-M25-20	M25×1.5	G3/4	NPT3/4	15 ~ 20	11 ~ 15	15
DEX2-M25-25	M25×1.5	G3/4	NPT3/4	17 ~ 25	15 ~ 20	15
DEX2-M32-25	M32×1.5	G1	NPT1	17 ~ 25	15 ~ 20	15
DEX2-M40-32	M40×1.5	G1-1/4	NPT1-1/4	23 ~ 32	18 ~ 26	15
DEX2-M50-40	M50×1.5	G1-1/2	NPT1-1/2	34 ~ 40	28 ~ 32	15
DEX2-M63-50	M63×1.5	G2	NPT1-1/2	44 ~ 50	35 ~ 45	15
DEX2-M75-66	M75×2.0	G2.5	NPT2.5	58 ~ 68	48 ~ 58	20
DEX2-M90-78	M90×2.0	G3	NPT3	68 ~ 78	56 ~ 67	20

双密封产品尺寸表/Double seal Product size

蓝江产品型号	螺纹规格/Thread size			电缆范围/Cable range		螺纹长度
				带铠电缆	内部电缆	
Product model	公制牙 M	英制牙 G	美制牙 NPT	Armored cable	Internal cable	Thread L
PN.	Metric	G(PF)	NPT	φ mm	AG mm	GL mm
SKZEX-M20-16	M20×1.5	G1/2	NPT1/2	12 ~ 16	6 ~ 10	15
SKZEX-M20-20	M20×1.5	G1/2	NPT1/2	15 ~ 20	11 ~ 15	15
SKZEX-M25-20	M25×1.5	G3/4	NPT3/4	15 ~ 20	11 ~ 15	15
SKZEX-M25-25	M25×1.5	G3/4	NPT3/4	17 ~ 25	15 ~ 20	15
SKZEX-M32-25	M32×1.5	G1	NPT1	17 ~ 25	15 ~ 20	15
SKZEX-M40-32	M40×1.5	G1-1/4	NPT1-1/4	23 ~ 32	18 ~ 26	15
SKZEX-M50-40	M50×1.5	G1-1/2	NPT1-1/2	34 ~ 40	28 ~ 32	15
SKZEX-M63-50	M63×1.5	G2	NPT1-1/2	44 ~ 50	35 ~ 45	15
SKZEX-M75-66	M75×2.0	G2.5	NPT2.5	58 ~ 68	48 ~ 58	20
SKZEX-M90-78	M90×2.0	G3	NPT3	68 ~ 78	56 ~ 67	20