

## 内牙尼龙防水波纹管接头

- 产品材料：尼龙
- 防护等级：IP68
- 工作温度：-40°~105°，短时可达120°
- 阻燃等级：UL94V-2 阻燃
- 订购说明：



- 1) 标配螺母，无需请联系客服说明
- 2) 默认黑色，可选灰白色
- 3) 产品价格为（人民币：元/套，美元：USD/set）

## Female nylon waterproof cable conduit connector

- Product material: nylon
  - Protection grade: IP68
  - Working temperature: - 40 °~105 °, up to 120 ° in a short time
  - Flame retardant grade: UL94V-2 flame retardant
  - Ordering Instructions:
- 1) Standard nut, no need to contact customer service for instructions
  - 2) Default black, gray and dark gray can be selected
  - 3) The product price is (RMB: yuan/set, USD: USD/set)

### 产品尺寸表/Product size

蓝江产品型号	螺纹规格	电缆范围	螺纹长度
Product model	Thread size	Cable range	Thread length
PN.	Metric	φ mm	GL mm
RQF-G1/4-AD10.0	G1/4	AD10	9
RQF-G3/8-AD13.0	G3/8	AD13	15
RQF-G1/2-AD15.8	G1/2	AD15.8	15
RQF-G1/2-AD18.5	G1/2	AD18.5	15
RQF-G1/2-AD21.2	G1/2	AD21.2	15
RQF-G3/4-AD21.2	G3/4	AD21.2	15
RQF-G3/4-AD25.0	G3/4	AD25.0	15
RQF-G3/4-AD28.5	G3/4	AD28.5	15
RQF-G1-AD34.5	G1	AD34.5	15
RQF-G1-1/4-AD42.5	G1-1/4	AD42.5	15
RQF-G1-1/2-AD54.5	G1-1/2	AD54.5	15
RQF-G2-AD54.5	G2	AD54.5	15

## 内牙加长防水波纹管接头

- 产品材料：尼龙
- 防护等级：IP68
- 工作温度：-40°~105°，短时可达120°
- 阻燃等级：UL94V-2 阻燃
- 订购说明：
  - 4) 标配螺母，无需请联系客服说明
  - 5) 默认黑色，可选灰白色
  - 6) 产品价格为（人民币：元/套，美元：USD/set）



## Female nylon long cable conduit connector

- Product material: nylon
- Protection grade: IP68
- Working temperature: - 40 °~105 °, up to 120 ° in a short time
- Flame retardant grade: UL94V-2 flame retardant
- Ordering Instructions:
  - 1) Standard nut, no need to contact customer service for instructions
  - 2) Default black, gray and dark gray can be selected
  - 3) The product price is (RMB: yuan/set, USD: USD/set)

### 产品尺寸表/Product size

蓝江产品型号	螺纹规格	适配软管	螺纹直径	螺纹长度
Product model	Thread size	Hose	Thread diameter	Thread length
PN.	Metric	φ mm	AG mm	GL mm
RQF-M20-AD13.0	M20×1.5	AD13	20	17
RQF-M20-AD15.8	M20×1.5	AD15.8	20	17
RQF-M20-AD18.5	M20×1.5	AD18.5	20	17