

RGW 带锁紧尼龙波纹管弯头

•产品材料：尼龙

•防护等级：IP65/IP68

•工作温度：-40°~105°，短时可达120°

•阻燃等级：UL94V-2 阻燃

•订购说明：

1) 标配螺母，无需请联系客服说明

2) IP65 应对波纹管，IP68 应对电缆锁紧

3) 产品价格为（人民币：元/套，美元：USD/set）



RGW cable conduit elbow connector with locking

•Product material: nylon

•Protection grade: IP65/IP68

•Working temperature: - 40 °~105 °, up to 120 ° in a short time

•Flame retardant grade: UL94V-2 flame retardant

•Ordering Instructions:

1) Standard nut, no need to contact customer service for instructions

2) IP65 shall be applied to corrugated pipe and IP68 shall be applied to cable locking

3) The product price is (RMB: yuan/set, USD: USD/set)

产品尺寸表/Product size

蓝江产品型号	螺纹规格	电缆范围	适配软管	螺纹长度	扳手尺寸
Product model	Thread size	Cable range	Adapter hose	Thread length	Wrench Size
PN.	Metric	φ mm	AD mm	GL mm	nut/cap mm
RGW15.8-MG16-10	M16×1.5	6~10	AD15.8	10	22/22
RGW15.8-MG16L-07	M16×1.5	4~7	AD15.8	10	22/22
RGW21.2-MG20-14	M20×1.5	8~14	AD21.2	15	27/27
RGW21.2-MG20-12	M20×1.5	6~11	AD21.2	15	27/27
RGW25-MG25-18	M25×1.5	13~18	AD25	15	33/33
RGW25-MG25-16	M25×1.5	11~16	AD25	15	33/33
RGW25-MG25-14	M25×1.5	8~14	AD25	15	33/33
RGW25-MG25-10	M25×1.5	6~10	AD25	15	33/33
RGW28.5-MG25-18	M25×1.5	13~18	AD28.5	15	33/33
RGW28.5-MG25-16	M25×1.5	11~16	AD28.5	15	33/33
RGW28.5-MG25-14	M25×1.5	8~14	AD28.5	15	33/33
RGW28.5-MG25-10	M25×1.5	6~10	AD28.5	15	33/33
RGW34.5-MG32-25	M32×1.5	18~25	AD34.5	15	41/41
RGW34.5-MG32-22	M32×1.5	16~22	AD34.5	15	41/41
RGW42.5-MG40-32	M40×1.5	24~32	AD42.5	20	50/50
RGW42.5-MG40-25	M40×1.5	18~25	AD42.5	20	50/50